

NATURAL HEATING

PRODUCT INFORMATION

- Insert coat made of boiler steel, with thickness of 3 mm, P265GH grade in accordance with EN 10028-2
- Steel doors made of special profile, guaranteeing rigidity and high-temperature resistance.
- Heat-resistant ceramic glass with working temperatures of up to 800 ° C.
- Steel base of insert fitted with an intake throttle of outside cold air.
- Insert equipped with air curtain, to guarantee the maintenance of a substantially pure glass effect.
- Specially designed rear part of the body, designed for secondary air supply to the upper part of the furnace. Allows to increase the efficiency of the device by after-burning the exhaust fumes.

RIGHT-SIDED HORIZONTAL FIREPLACE INSERT **ALBERO AL9R.H**

| | |
|---|--|
| Nominal power (kW) | 9 |
| Heating load range (kW) | 5-10 |
| Flue diameter (mm) | 180 |
| Heat performance (%) | 84,9 |
| CO emission (with 13% O ²) | 0,070 |
| Dust emission (g/m ³) | 0,038 |
| Exhaust emission (°C) | 194 |
| Weight (kg) | 107 |
| Log maximum length (cm) | 30 |
| Material | boiler steel with thickness of 3 mm P265GH |
| Fuel Type | hardwood, briquettes, lignite |
| Min. Active field of exhaust grilles (cm ²) | 900 |
| Min. Active field of intake grilles (cm ²) | 700 |
| Size of fireplace glass (mm) | 545 x 390 x 325 |

